Tek-Industrial
Touchscreen Solutions

# PC6N2

Multifunctional Box PC



## Compact and VESA-Ready

:PC6N2 features a sleeker, more compact design, saving space without compromising on performance. With VESA mount compatibility at 100x100mm, you can effortlessly set up your KPC6N2 wherever youlesire.










Windows Linux android

*A Smarter Solution for a Connected World*

# Specifications

| | | F35 |
|---|---|---|
| System | Motherboard | F35 |
| | Processor | Intel® Elkhart Lake Celeron J6412 |
| | Memory | 1x DDR4 up to 8GB |
| | Storage | 128GB SSD (M.2) |
| | Expansion | M.2 (E Key) 1 |
| Front I/O Ports | Power Button | 1 |
| | HDMI | 2 |
| | Line-out | 1 |
| Rear I/O Ports | USB Type-A | 2x USB3.0, 4x USB2.0 |
| | USB Type-C | 1x USB3.0 full-functioned (DP / PD 5V/3A, 12V/3A) |
| | FeDP | 1x Tek-Industrial proprietary miniDP |
| | Serial Port | 3x RJ48 (standard RS232) (default 0V; 5V, 12V) |
| | LAN | 1x RJ45 |
| | Power Button | 1 |
| | DC Jack | 1x 4PIN (with latch) |
| Indicator | LED Indicator | 1 |
| | Power Button | 1 |
| Power | Power Adapter | 65W / 19V |
| Communication | WLAN + BT | 802.11 series + BT5.0 (Option) |
| Certificate | EMC & Safety | FCC Class A, CE Mark, LVD |
| Environment | Operating Temperature | 0°C ~ 35°C (32°F ~ 95°F) |
| | Storage Temperature | -20°C ~ 60°C (-4°F ~ 140°F) |
| | Humidity | 20% ~ 85% RH non-condensing |
| Mounting | VESA Mount | 100 x 100 mm |
| OS Supported | | Windows 10 or 11 IoT / Linux / Android 13.0 |

※ Product specifications and data are subject to change without notice.

Tek-Industrial
Touchscreen Solutions

*Innovation Today*
*for a Smarter Tomorrow*